Product data sheet

TS 5000 L-R

Overhead door closer with guide rail, for opposite hinge side, for single leaf doors of up to 1400 mm leaf width with electric hold-open device and smoke switch

GEZE GmbH | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | **TEL** +49 7152 203-0 | **WEB** www.geze.de | **Mail** info.de@geze.com

Product features

Closing force of EN2-6 with variable adjustment
Operating voltage 24 V DC
Can be used for right and left hand doors without conversion
Electric hold-open device in the guide rail with hold-open area of 80°-130°
Integrated smoke switch control unit, whose signal closes the door automatically in the event of a fire
Smoke switch with contamination indicator and adaption of the alarm threshold
Additional smoke detectors may be fitted
Hydraulic latching action which accelerates the door shortly before the closed position
Closing speed can be individually adjusted
Integrated back check, slows down doors that are thrown open forcefully
Visual closing force display for easy control of the setting
All functions can be adjusted from the front

Application Areas

Right and left single-action doors
Single-action doors up to 1400 mm leaf width
Door leaf installation opposite hinge side
Hold-open systems with integrated hold-open device

Product Data Table

Productname	GEZE TS 5000 L-R
Suitability for fire protection doors	Yes

Accessory

Product name
Cover cap door closer
GEZE GC 152 smoke detector
GEZE GC 153 thermal detector
Surface-mounted box, single
Interruption switch AS 500
GEZE GC 171 wireless module
GEZE GC 175 wireless input module
GEZE GC 172 wireless smoke detector
GEZE GC 173 wireless thermal detector
GEZE GC 170 Wireless KIT

Part

Product name
R-guide rail BG TS 5000
GEZE TS 5000 L Closer